# KREISI metall











# trailer

Crane and log bolster posts can be moved on the main frame to adjust the load balance of that trailer. The loading bed can also be additionally extended for the length of 0.5 or 1.0 m after which it is possible to transport logs with a length up to 5.0 m

Maximum load at 25 km/h - 1500 kg.

Maximum speed - 30 km/h
Loading area - 2.400 m
Length - 3.809 m
Width - 1.252 m
Tires - 22x11-8
Weight - 170 kg.



#### Tipping box:

The tipping box can be easily mounted on the trailer. The box is connected to the frame with belts - it is fast and flexible.

Low weight and durability is achieved by using strong plastic at the bottom and sides of tipping box.

Weight - 150 kg.

Maximum load - 1000 kg.

Maximum opening angle - 46 degrees

Dimensions - W / L / H - 127/200/29,5 cm



# grapple loader

#### Grapple loader Vahva Jussi 320

Grapple is made robust and reliable, with low weight and high durability.

Hydraulic distributor -5/7 XY Radius of rotation -330 degrees Maximum reach of the crane -3,2 m Radius of rotation of the rotator infinite Maximum weight lifting at 3.2 m -280 kg. Rotator GR10 -1 T Maximum weight lifting at 2.0 m -0.08 m2 415 kg. Grapple -Maximum lifting force -550 kg. Maximum opening of grapple -750 mm. Weight -150 kg Maximum oil pressure -175 bar



#### Grapple loader Vahva Jussi 400

Grapple is made robust and reliable, with low weight and high durability. It has a telescopic extension for greater maneuverability and accessibility.

Hydraulic distributor -6/8 XY 4,0 m Maximum reach of the crane -Maximum weight lifting at 3.2 m -260 kg. Maximum weight lifting at 2.0 m -385 kg. Maximum lifting force -530 kg. 175 bar. Maximum oil pressure -330 degrees Radius of rotation infinite Radius of rotation of the rotator -Rotator GR10 -1 T Grapple -0.08 m2 Maximum opening of grapple -750 mm. 170 kg Weight -





#### **Trailer frame extension:**

Required when transporting logs up to 5 m long. Two sizes of frame extensions: 0.5 m and 1.0 m **Yellow bolster post extension**: Required for energy wood and branch transport

# Different accessories to use with the log crane

# Log grapple: \_\_\_\_\_

- Strong and reliable, made with low weight and greater durability
- Maximum opening 750 mm.
- Capacity 0.08 m<sup>2</sup>
   The weight 27 kg.



## Energy wood grapple: \_\_\_\_\_

Ideal for small forest holdings; cleaning woodland, vineyards, gardens or ditches. Upon removal of one bolt and blade it can be used as an ordinary log grapple.

Working oil pressure - 170-190 bar.

Maximum oil pressure - 210 bar.

Weight - 52 kg.

1 ton rotator adapter - Ø 39,5 mm.

3 tons rotator adapter -  $\varnothing$  49,5 mm. Maximum cutting diameter - 12 cm

Cutting edge - Hardox 500



#### Earth bucket:



Capacity - 60 liters Weight - 60 kg



# Earth drill for holes:

Ideal for drilling holes in soft ground, such as building fences.

Three sizes: Ø 100 mm

Ø 150 mm

∅ 200 мм





As additional equipment the crane can be equipped with a radio controlled hydraulic winch:

### Radio controlled hydraulic winch: \_\_\_\_\_

The winch helps to pull the logs closer from inaccessible and dangerous places.

Operating range of the remote control - 25 m Weight - 11 kg.

Wire Rope - Length 25 m, 5mm thick

Pulling speed - 35 m. / Min.
Pulling force - 435 kg.



As optional equipment on the trailer you can install 4x4 hydraulic drive system.

# 4x4 hydraulic drive system: \_\_\_\_\_



Helps an ATV/UTV to move in snow, mud, steep and slippery slopes. Can be used as a brake on the decents.

Maximum movement speed - 3 km/h
Pushing force of 4WD - 650 kg
Min oil pressure - 175bar
Min oil flow - 9 L/min





## Honda 5,5hp hydraulic unit with manual starter: \_\_\_\_

#### Specifications:

Engine - 4-stroke Honda GX160

Power - 5.5 hp Weight - 38 kg.

Dimensions - 65 x 40 x 40 cm

Fuel tank - 3,5 I



# Honda power pack with electric starter and battery: —

Powers crane and other equipment that needs oil for operation.

Description:

Engine - 4-stroke Honda GX200

Power - 6.5 hp Weight - 50 kg.

Dimensions - 65 x 45 x 40 cm

Fuel tank - 3,5 I



# ... another possibility to use a hydraulic pump on your tractor PTO:













# You can use a variety of vehicles . . . . . . . . .

### small tractors





# 4x4 cars and Pick-Up's





### Iron Horse





### ATV or UTV



and others . . .





- forestry
- agriculture
- gardening and Landscapinglivestock
- vineyards
- construction













ideal for use in nature protected areas and parks









Manufacturer of Vahva Jussi products

# KREISI METALL OÜ

Metsavahe tee 2, Näpi, Lääne-Virumaa, Estonia www.kreisi.ee info@kreisi.ee